SOMA TECHNOLOGY, INC.[™] New, Demo & Refurbished Medical Equipment

The color display has a wide viewing angle, and excellent visibility from a distance, so you can easily recognize and see the data you need for decision making. For applications where a larger display is required, an additional display can be connected to the monitor via the standard VGA output. The Philips Agilent Viridia M3 patient monitor is designed for use by clinicians for adult, pediatric and neonatal patients in Critical and Intermediate Care areas, in Operating Rooms and General Wards, and for transport inside and outside the hospital.

Features

- Portable
- Wireless
- Networked monitor
- EASI[™]-derived 12-lead ECG4 using a 5-electrode cable set
- Multi-lead Arrhythmia
- Up to 3 channels of ECG with basic Arrhythmia and ST Analysis capability
- FAST-SpO2 measurement, using Fourier Artifact Suppression Technology, for accurate performance even with low perfusion
- Respiration, Non-invasive and Invasive Blood Pressure, and Temperature measurements
- Mainstream or Sidestream CO2, a second Invasive Blood Pressure and Temperature measurements, and enhanced Arrhythmia capability, available optionally



Soma Technology Inc. • 166 Highland Park Drive • Bloomfield, CT 06002 • USA Phone: 1.800.GET.SOMA • www.SomaTechnology.com • Email: soma@somatechnology.com



Specifications

•	
Dimensions	Without Handle
	Width: 8.27 in (210 mm)
	Height :8.27in (210 mm)
	Depth: 5.31 in (135 mm)
	Weight: with out battery 7.05 lbs. (3200 g)
Electrical	100 to 240VAC, 50/60Hz,
	0.4 to 0.7A
Display	6.5" (diagonal) active color LCD (TFT)
	Resolution: 640×480 pixels
VGA Interface	Refresh rate: 60 Hz.
	Horizontal frequency: 31.5 kHz
	Resolution: 640 x 480 pixels
	Video Signal: 0.7 Vpp @ 75 Ohm
	HSYNC/VSYNC signal type: TTL
	Connector: 15-pin D-SUB

Soma Technology Inc. • 166 Highland Park Drive • Bloomfield, CT 06002 • USA Phone: 1.800.GET.SOMA • www.SomaTechnology.com • Email: soma@somatechnology.com

