



Use up to 6 instruments, support app, 19 optimized modes, new VIO 3 modes: preciseSECT low smoke exposure, thermoSEAL rapid vessel sealing, highCUT bipolar resection, softCOAG accelerated coagulation, Wi-Fi communication interface

Features

- Logical, convenient and visual operator guidance (stepGUIDE)
- Reliable, reproducible tissue effects thanks to state-of-the-art processor technology
- ReMode: up to 6 different settings selectable from the sterile field
- Sockets: easy replacement, connection recommendations, slot assignment, up to 6 instruments freely selectable



Specifications

Dimensions

Width x Height x Depth: 415 x 215 x 375 mm

Display Size: 10.4 inches

Weight: 12k

Power Connection

Rated supply voltage: 100-120 VAC ($\pm 10\%$), 220-240 VAC($\pm 10\%$)

Rated supply frequency: 50 / 60 Hz

Line current (average): Max. 6.3 A

Power consumption in standby mode: < 30 watts

Power consumption at max. Hf power: 550 watts

Max. Power consumption: 1,600 watts

Potential equalization connection: Yes

Power Fuse: T 6.3 A H /250 VAC

Type of Operation

Intermittent operation: 25% duty cycle

Ambient Conditions for transport and Storage of the unit

Temperature: - 30 °c to +70 °C

Relative humidity: 10% - 90%

Ambient condition for operating the unit

Temperature: + 10 °C to +40 °C

Relative Humidity: 15% - 80%, non-condensing

Standards

Classification in accordance with EU directive 93/42/EEC: II b

Protection class in accordance with EN 60 601-1: I

Type in accordance with EN 60 601-1: CF

Programs

Program groups: 20; program storage capacity per group: 15

Programs / applications: Up to 300

ReMode Levels / settings: Up to 1800