

The **GE B125** is one of the newest patient monitors from GE. The B125 monitor is known for its simplistic design, with its large 12-inch, captive touch screen. Making it easy for caregivers to interpret and modify patient data promptly. The large numerical or continuous waveforms and easy to see from any angle. The monitor comes standard with advanced parameter monitoring includes; ST-segment analysis, Full arrhythmia analysis, TruSignal SpO2, SuperSTAT NIBP, IBP, Respiratory rate, 3 or 5 Lead ECG, and EtCO2. The GE B125 can be a stand-alone monitor or it can be used along with other devices in a network.

## **Features**

- ST-Segment and full Arrhythmia analysis, SpO2, NIBP, IBP, RR, ECG, and EtCO2.
- Records and stores up to 168 hours of monitoring activities across all parameters.
- · Analyses up to 16 types of arrhythmia including AFib.
- Three-hour battery life for optimal uninterrupted monitoring.
- A large numeric mode that enables critical parameter visibility even up to 13-feet away.
- 12.1" Display



SOMA TECH INTL • 166 HIGHLAND PARK DRIVE • BLOOMFIELD, CT 06002 • USA PHONE: 1.800.GET.SOMA • WWW.SOMATECHNOLOGY.COM • EMAIL: SOMA@SOMATECHNOLOGY.COM

## **GE B125**Patient Monitor

## Specifications

**Dimensions** Height: 11 in (280 mm)

Width: 12.5 in (317 mm) Depth: 5.9 in (150 mm)

Weight: 9.5 lbs (4.3kg) (with battery)

**Display** Size: 12.1 in (diagonal)

Resolution: 1280 x 800 pixels Number of waveforms: Up to 6

Display layout and Color: User-configurable

Controls: Capactive Touch Screen & trim knob control and hand keys

Paper recorder Temperature: 5 to 40°C (41 to 104°F)

Relative Humidity: 20 to 90% noncondensing

Atmospheric Pressure: 700 to 1060 hPa (525 to 795 mmHg)

**Operating Conditions** 100–120 +/- 10% VAC with "100–120V" selected on the supply voltage

elector

220-240 +/- 10% VAC with "220-240V" selected on the supply voltage

selector 50–60 Hz

530 VA

Storagr and Transport

Conditions

Temperature: -20 to 60°C (-4 to 140°F)

Relative Humidity: 10 to 90% noncondensing

Atmospheric Pressure: 700 to 1060 hPa (525 to 795 mmHg)

Power Specifications AC Input: 100 to 240V ±10%, 50/60 Hz, 150VA

Protection: Class I

Battery: Exchangeable lithium-ion, 1 pcs max

Charging Time: < 4 h to 90% capacity

Run Time: > 3 h

