



The Maquet Datascope CS300 IABP with IntelliSense combines fiber-optic speed with automatic in vivo calibration. The result is faster time to therapy, faster signal acquisition, and faster adaptation to rate and rhythm changes. Maquet has the only fiber-optic IABP and catheter system that automatically calibrates in the patient after insertion and automatically recalibrates in vivo every two hours or sooner should patient or environmental conditions change.

Features

- Faster inflation and deflation speed
- CS300 has true one-button start-up
- Automatically calibrates the fiber-optic pressure sensor in the patient and recalibrates every 2 hours or sooner should patient or environmental conditions change
- Automatically evaluates and selects the best lead and trigger source
- Automatically sets optimal timing
- Automatically adjusts to changes in patient conditions without clinician intervention
- A Maquet fiber-optic IAB catheter
- Conventional fluid-filled IAB catheters



Specifications

Dimensions

Size on Cart: 43.1" H x 22.3" D x 16.8" W (109 cm H x 56.6 cm D x 42.7 cm W)
Size off Cart: 26.9" H x 20.5" D x 10.8" W (68.3 cm H x 52.1 cm D x 27.4 cm W)
Console Weight: 84.8 lbs. (38.4 Kg) nominal (includes S.D., CRM, and He tank)
Monitor: 9.5 lbs. (4.3 Kg) nominal
Hospital Cart Weight: 52.4 lbs. (23.8 Kg) nominal
Internal Battery: 34 lbs. (15.4 Kg) nominal
Storage Bag: 4.6 lbs. (2.1 Kg) nominal (includes doppler and doppler holder)

Color Display

Color TFT Liquid Crystal Display (LCD) 8.3"(21cm)W x 6.2"(15.8cm)H; up 45°, 10.4" diagonal (26.4 cm) down 55°, right 70°, left 70° viewing angle; Rotates 330°; Tilts 180°; Detachable; Laptop-like closure for storage and protection; Remote monitor mount (optional)

Trigger

ECG Trigger: Threshold dynamically adjusted by system for high sensitivity and selectivity of the R-wave detection; Minimum = $120\mu\text{V} \pm 20\mu\text{V}$ at normal gain; $40\mu\text{V}$ at max. gain
Pressure Trigger: Default trigger threshold is automatically adjusted to 38% of the systolic pulse height; 7 mm minimum
Manual threshold mode: User adjustable between 7 and 30 mmHg ± 3 mmHg
Pacer A Trigger: R-wave detection (as above) except pacer blanking is extended to 100 ms
Pacer V/A-V Trigger: V Pacer: fixed at rate up to 185 bpm (no demand pacing)
A-V Pacer: fixed at rate up to 125 bpm (no demand pacing) with A-V intervals between 80-224 ms

Power

Mains Voltage: 100-120 VAC $\pm 10\%$ or 220-240 VAC $\pm 10\%$
Mains Frequency: 50/60 Hz ± 3 Hz
Internal Battery: 24 VDC (nominal), 17.2 Amp-hour, approx. 3 hrs. @ 90 bpm
Battery Type: Maintenance free; Sealed lead-acid

Pressure

Pressure Output: (electrically isolated)
Pressure Range: 0 to +300 mmHg (minimum)

Operating

Op. Temp.: 10°C - 40°C
Op. Humidity: 5 - 95% (R.H.) non-condensing
Op. Altitude: 0 - 12,000 feet (3,657 m); automatic altitude correction for IAB pressure

ECG

ECG Leads: In Auto Operation Mode: I, II, III, External In Semi-Auto Mode: I, II, III, AVR, AVL, AVF, V, External (12 lead compatibility)
ECG Gain (default): 1 V output per 1 mV input $\pm 5\%$ (waveform automatically scaled to occupy ECG display window)
Gain (variable): 0.15 to 3.0 cm/mV $\pm 20\%$ (autoscaling disabled)
Frequency Response: 0.5-12 Hz (display); 0.5-135 Hz (Output to External Monitor)
Defibrillator Protection: Discharge level ≤ 360 J (trace returns to screen in 5 sec max)
ESIS: Automatic suppression with internal ECG amplifier