Medtronic 5391
Temporary External Pacemaker

The **Medtronic 5391** is a single-chamber temporary pacemaker that provides four different types of modes for pacing therapy. This Medtronic pacemaker is battery-powered and used for atrial or ventricular pacing. It has a basic pacing rate of 180 ppm. The device is ergonomically designed to allow easy set-up. A single 9V battery can run the device up to 38 days.

Features

- Operates with a 9V alkaline battery.
- VVI, AAI, VOO, and AOO pacing therapy modes.
- Compatible with Medtronic 6416, Medtronic 53912, Medtronic 5433A, and Medtronic 5433V pacing leads, extension cables, and patient cables.

SOMA TECH INTL • 166 HIGHLAND PARK DRIVE • BLOOMFIELD, CT 06002 • USA
PHONE: 1.800.GET.SOMA • WWW.SOMATECHNOLOGY.COM • EMAIL: SOMA@SOMATECHNOLOGY.COM

REVISED 1/6/2022

Medtronic 5391
Temporary External Pacemaker

Specifications

Dimensions	**Height:** 4.5 in. (11.5 cm) **Width:** 2.3 in. (6 cm) **Depth**: 0.8 in. (2 cm) **Weight** (with battery): 6.5 oz (185 g)
Battery Life	**Alkaline:** 38 days **Lithium:** 53 days
Modes	**Modes:** VVI, VOO, AAI, AOO
Rates	**Pacing Rate:** 30 - 180 ppm **Atrial Overdrive Pacing** (RAP): x2: 60 - 360 ppm; x4: 120 - 720 ppm
General	**Output Amplitude:** 0.3 … 12 V ± 5% **Pulse Width:** 0.75 ms ± 0.02 ms **Sensitivity:** 1 - 20 mV, Async **Refractory:** 250 ms

SOMA TECH INTL • 166 HIGHLAND PARK DRIVE • BLOOMFIELD, CT 06002 • USA
PHONE: 1.800.GET.SOMA • WWW.SOMATECHNOLOGY.COM • EMAIL: SOMA@SOMATECHNOLOGY.COM

REVISED 1/6/2022