



The intuitive design and user-friendly set-up of the Mega Power Electrosurgical Generator (diathermy) allows your surgical team to hit the ground running. The confusion and frustration associated with previous generators are a thing of the past. Surgical teams have been asking for a generator that is simple, intuitive to use, and easy to set-up.

Features

- Large, easy to read displays. Highly visible, even at a distance.
- Recall feature readily recalls previous power settings and modes on set-up.
- Quick scroll feature allows for fast and accurate power setting adjustments.
- Power switch is easily accessible on front panel of generator.
- Highly visible return electrode warning light.
- 6 clearly labeled and easily selectable mode settings. (APTT)



Specifications

Dimensions

Height: 7.9 in (20 cm)
Width: 15.9 in (40.5cm)
Depth: 15.9in (40.5 cm)
Weight: 19 lbs (8.65 kg)

Operation Environment

Temperature Range: +10°C (+50°F) to +40°C (+104°F)
Humidity Range: 15% to 75% Non-condensing
Atmospheric Pressure: 700 hPA (10.2 psi) to 1060 hPA (15.37 psi)

Storage Environment

Temperature Range: -40°C (-40°F) to +70°C (+158°F)
Humidity Range: 10% to 100 %, Condensing
Atmospheric Pressure: 500 hPA (7.25 psi) to 1060 hPA (15.37 psi)

Audio Frequencies

ACE Cut, Pure CUT and Blend 840 Hz ± 10%
Standard Coag and Spray Coag 520 Hz ± 10%
Bipolar 480 Hz ± 10%

Alarms

Power Limit (One beep) 1980 Hz ± 10%
Errors (Two beeps) 1980 Hz ± 10%
CQM (Three Beeps) 2550 Hz ± 10%