



The **Midmark Ritter m9** sterilizer has a small compact footprint. Pack all the reliable sterilizing power you need into one small compact unit, perfect for limited spaces. The M9 UltraClave features a LCD display that comes with simple prompts that help you easily select the cycle that is needed. Once the sterilization cycle is over the door will automatically open to allow the steam to dissipate. This allows the instruments to dry efficiently. The Midmark has four defining cycles; unwrapped items, pouches, packs and hand pieces, along with customizable cycles with a self-program control.

## Features

- Exclusive automatic-opening door for ease of use and a quick drying time
- Steam-Flush Pressure Pulse Air Removal System ensures proper steam penetration
- Self Program Controls enable you to create different cycle parameters to meet specific instrument processing needs
- Pre-Programmed Controls for convenience
- LCD Display for easy view of indicators



# Specifications

## Dimensions

Overall length w/plug: 20.4" (51.8 cm)  
Overall width: 15.3" (38.9 cm)  
Overall height w/printer: 15.8" (40.1 cm)  
Minimum Countertop area: 15.3" x 17.9" (38.9 cm x 45.4 cm)

## Chamber

9" diameter (22.9 cm)  
15" depth (38.1 cm)  
3.5 gal. usable volume (13.4 liters)

## Tray Capacity

Two large – 7.3"W x 12" L x .8" D (18.6 cm x 30.5 cm x 2.2 cm)  
Two small – 5.6" W x 12" L x .8" D (14.3 cm x 30.5 cm x 2.2 cm)

## Weight

Unit weight: 73 lbs. (33.1 kg)  
Shipping weight: 81 lbs. (36.7 kg)  
Water reservoir capacity: 1.1 gal. (4.1 liters)

## Electrical Requirements

115 VAC, 50/60 Hz, 15 Amps Single Phase  
115 VAC has 1425 watt tubular immersion heater

## Safety Standards

115 VAC, 50/60 Hz, 15 Amps Single Phase  
115 VAC has 1425 watt tubular immersion heater

