

The Olympus SurgMaster Electrosurgical Unit UES-40 offers significantly improved performance in cutting and coagulation for electrosurgery. Allowing the use of conventional monopolar resectoscopes as well as bipolar and monopolar hand instruments, the UES-40 also enables resection in saline procedures.

The UES-40 is compatible with the SonoSurg Ultrasonic Surgical System, allowing high-frequency output using its transducer, further expanding surgical possibilities.

Features

- · Solid and reliable performance
- Automatic smoke evacuation available
- Dual resection mode



Soma Technology Inc. • 166 Highland Park Drive • Bloomfield, CT 06002 • USA Phone: 1.800.GET.SOMA • www.SomaTechnology.com • Email: soma@somatechnology.com

Olympus UES 40 Electrosurgical Unit

Specifications

Dimensions Width: 350 mm

Height: 150mm Length: 400 Weight: 12 kg

Power Voltage 100 – 120 V

Frequency 50/60 Hz Input current 12 A

Voltage

fluctuationWithin 10%

Operating Environment Ambient temperature 10 – 40\(\text{MC} \) (50 – 104\(\text{MF} \))

Relative humidity 30 – 85%

Atmospheric pressure 700 – 1060 hPa

Storage Environment Ambient temperature -25 to +70\mathbb{MC}

 $(-13 \text{ to } + 158 \boxtimes F)$

Relative humidity 10 – 90%

Atmospheric pressure 700 – 1060 hPa

Soma Technology Inc. • 166 Highland Park Drive • Bloomfield, CT 06002 • USA Phone: 1.800.GET.SOMA • www.SomaTechnology.com • Email: soma@somatechnology.com