Philips PageWriter Touch ECG System



The **Philips Pagewriter Touch** is an electrocardiograph system that was designed for hospital use. The Pagewriter Touch offers accurate, high-quality EKG reading. The 15-inch color touch screen display can easily and quickly show a snapshot of an ECG reading before printing. The Pagewriter Touch uses the Philips 12-leads to produce 10 seconds of a clear EKG. The system offers wireless connectivity that allows the patient's data to be transferred from the EKG to the data storage system in your medical facility.

Features

- Easy, Fast, 12-Lead ECGs for Large or Small Hospitals
- Designed for high volume
- High resolution touch screen
- Preview reports before printing
- Wireless communication



SOMA TECH INTL • 166 HIGHLAND PARK DRIVE • BLOOMFIELD, CT 06002 • USA PHONE: 1.800.GET.SOMA • WWW.SOMATECHNOLOGY.COM • EMAIL: SOMA@SOMATECHNOLOGY.COM



Philips PageWriter Touch ECG System

Specifications

Dimensions	Length: 17.7 in (45cm) Width:18in (45.8 cm) Height: 6.34 in (16 cm) Weight: Aprox. 13 kg (28 lbs) including accessories
EKG Acquisition	R/T (real-time) ECG (12 leads) AUTO (12 leads) RHYTHM (up to 12 leads) DISCLOSE (1 to 3 leads)
Touch Screen Display	1024 x 768 pixel resolution 30.4 cm x 22.8 cm (15-inch diagonal) color liquid crystal touch screen display with backlight
Paient Module	Action button allows user to take EKG snapshots from the bedside
Auto Frequency Response	0.05-150 Hz, 0.15-150 Hz, 0.5-150 Hz, 0.05-100 Hz, 0.15-100 Hz, 0.5-100 Hz, 0.05-40 Hz, 0.15-40, 0.5-40 Hz
Rhythm Frequency Response	0.05-150 Hz, 0.15-150 Hz, 0.05-100 Hz, 0.15-100 Hz, 0.05-40 Hz, 0.15-40 Hz
Filters	AC noise Baseline wander Artifact
Printer/ Printer resolution	High-resolution, digital-array printer using thermal sensitive paper 200 dpi (voltage axis) by 500 dpi (time axis)
Battery Operation Capacity	Typically 50 EKGs and copies on a single charge or 40 minutes of continuous rhythm recording Recharge Seven hours in standby mode to >90% capacity (typical)
Network Connection	10/100 Base-T IEEE 802.3 Ethernet via RJ45 connector (standard) Optional software required for Proxim Range LAN2 7410 CE PC card wireless LAN connection (Wireless PC LAN card not included)

SOMA TECH INTL • 166 HIGHLAND PARK DRIVE • BLOOMFIELD, CT 06002 • USA PHONE: 1.800.GET.SOMA • WWW.SOMATECHNOLOGY.COM • EMAIL: SOMA@SOMATECHNOLOGY.COM

