



The **Skytron 3003 IP** imaging table features an 83" carbon fiber top for full body imaging. The table offers a 65" window for unobstructed imaging, and the two-speed, multidirectional top slide means the patient can be effortlessly moved throughout the imaging window at the command of the joystick control. The 3003 also features a low profile base that will not conflict with movable imaging equipment..

Features

- Offers 20" longitudinal and 8" lateral top slide
- 500 lb lift and articulation weight capacity
- Two-speed joystick control operates table movement
- Table height adjustable from 28" - 42"
- 83" carbon fiber top
- 65" unobstructed imaging window
- 20° lateral tilt, Trendelenburg and reverse Trendelenburg
- Recommend for endo vascular imaging or stent placement



Specifications

Physical

Length: 83" (2,100 mm)
Width: 19 5/8" (500 mm)
Width: With side rails 22" (560 mm)

Adjustments via hand control

Height: 28"-42" 710-1065 mm
Lateral tilt (left/right): 20°
Trendelenburg: 20°
Reverse Trendelenburg: 20°
Return to level (return to horizontal position from articulated positions)
Base braking (lock/unlock)

Max permissible load

500 lb (227kg): Lift
500 lb (227kg): Articulation

Joy Stick Control

For operation, top button on joystick control must be depressed.

Max permissible load

500 lb (227kg): Lift
500 lb (227kg): Articulation

Orientation Button

Reverse Normal

Center Button

Moves table top to center position

Speed

High Low

Differentiating Features

- 20" longitudinal and 8" lateral top slide
- 500 lb lift and articulation weight capacity
- Two-speed, multidirectional joystick control
- 28" - 42" adjustable table height
- 83" carbon fiber top
- 65" unobstructed imaging window
- 20° lateral tilt
- 20° Trendelenburg and reverseTrendelenburg

