



The **Steris ASC 2000** surgical table is battery powered and specifically designed to provide the complete patient positioning flexibility required for modern ambulatory surgical care facilities. The ASC 2000 features powered lateral tilt, trendelenburg / reverse trendelenburg, and adjustable height functions. It is designed to safely function with a 400 lb. patient and is constructed of aluminum alloy, stainless steel, and other high quality materials.

Features

- 400 lb maximum patient weight.
- Equipped with an auxiliary control system.
- Toggle switches on the front of the table base are used for table movements as long as electrical power is still available.
- Manually adjustable headrest and leg sections.
- 79" total table length.
- 22" total table width.



Specifications

Dimensions

Height: 27.5 to 41 in (69.9 to 105.5 cm)
Width: 22 in (20.32 cm)
Length: 79 in (200.9 cm)
Weight: 485 lbs (220 kg)
Maximum Patient Weight: 400 lbs (181 kg)

Table Movements

Height: 27.5" to 41" (69.9 to 104.5 cm)
Trendelenburg Range: 45° ± 1°
Reverse Trendelenburg Range: 20° ± 1°
Lateral Tilt Range: 20° ± 1°
Lower Back Motion: UP: 75° ± 1°; DOWN: 15° ± 1°
Upper Back Motion: UP: 40° ± 1°; DOWN: 55° ± 1°
Head Motion (Manual): UP: 33° ± 1°; DOWN: 87° ± 1°
Leg Motion (Manual): UP: 0°; DOWN: 90° ± 1°; (Swivel 90° toward outside)

Power

Input: 100-132 VAC, One-Phase, 50/60 Hz, 5.0 A
Input: 180-264 VAC, One-Phase, 50/60 Hz, 3.0 A

Environmental

Temperature: 32 to 122°F (0 to 50°C)
Relative Humidity: 20 to 80% RH

