

The **Welch Allyn Schiller AT 2** is a 12-lead EKG system that can support a six-channel format. The AT 2 is a battery-operated system that can run up to 6 hours and provide full-size (8.5 x 11) report printouts. The EKG offers an LCD screen for quick previews and an alphanumeric keyboard for ease of use. The Cardiovit At 2 is a lightweight system, making it ideal for either a Physician's office or ambulatory field work.

Features

- 6 or 12-channel representation of all 12-leads
- · Automatic and Manual Modes
- Full size 8 x 11 report printouts (A4)
- Rechargeable battery
- can do 400 recordings on a fully charged battery
- Single button operation



SOMA TECH INTL • 166 HIGHLAND PARK DRIVE • BLOOMFIELD, CT 06002 • USA PHONE: 1.800.GET.SOMA • WWW.SOMATECHNOLOGY.COM • EMAIL: SOMA@SOMATECHNOLOGY.COM

Specifications

Dimensions Length: 15.7 in (400 mm)

Width: 13 in (330 mm)

Depth: 4 in (100 mm)

Weight: 11 lbs. (5 kg)

Power Battery:Built-in 12 V lead-acid battery (rechargeable)

Battery Capacity: 4 hours normal use - 300 printouts

Power Consumption: Recording: 28 VA max

ECG Storage Circular input memory for 10 s, 12-lead ECG.

ECG Amplifier Simultaneous, synchronous registration of all 9 active electrode signals (= 12

standard leads)

Sampling frequency: 1000 Hz

Digital resolution: $5 \,\mu\text{V}$ Dynamic range: $\pm 9.5 \,\text{mVAC}$

Max. electrode potential: ±300 mVDC

Time constant: 3.2 s

Frequency response: 0.05 to 150 Hz (-3 dB) Input impedance: >2.5MOhms at 10Hz

Environmental Conditions Temperature, Operating: 100 to 40 deg. C

Temperature, Storage: -10 deg. to 50 deg. C Relative humidity: 25 to 95% (non condensing) Atmospheric pressure: 700 to 1060 hPa

Other Specifications Leads: Standard / Cabrera

Paper Speed: 5 / 10/25 / 50 mm/s (direct)

Sensitivity: 5 /10 / 20 mm/mV, either automatically adjusted or manually

selected

Chart Paper: Thermoreactive - Z-folded, 210 mm wide, perforation 280 mm

Printing Process:

High-resolution thermal print head,

8 dots per mm / 200 dots per inch (amplitude axis) 40 dots per mm / 1000 dots per inch (time axis 25mm/s)

Recording Tracks: 6 channels, positioned at optimal width on 200 mm,

automatic baseline adjustment

Automatic lead Programs: Printout of all 12 leads Data Record: Listing of ECG recording data