

The **Welch Allyn Propaq CS 242** is a patient monitor that can also do Vital signs. The Propaq 242 features a 6 inch LCD touch screen display that can show up to 4 waveforms at once. The patient monitor offers measurements of 3-5 lead ECG, non-invasive blood pressure, SpO2, dual temperatures, and respiration rate. The monitor can be used for continuous monitoring of patients ranging from neonates, pediatrics, and adults.

Features

- 3 or 5-lead ECG monitoring.
- Continuous vital signs monitoring.
- Detects rate or absence of respiratory effort, deriving the signal by measuring the ac impedance between the selected terminals of the ECG electrodes.
- Noninvasive Blood Pressure (NIBP) monitoring.
- Temperature (TEMP) monitoring using and attachable probe.
- SpO2, CO2, and Recorder (Optional)





SOMA TECH INTL • 166 HIGHLAND PARK DRIVE • BLOOMFIELD, CT 06002 • USA PHONE: 1.800.GET.SOMA • WWW.SOMATECHNOLOGY.COM • EMAIL: SOMA@SOMATECHNOLOGY.COM

Welch Allyn Propaq CS 242 Vital Signs Monitor

Specifications

Dimensions (Monitor) Height: 8.2 in (20.8 cm)

Width: 9.6 in (24.4 cm)

Depth: 5.6 in (14.1 cm)

Weight: 7.6 lbs (3.4 kg)

Dimensions (Printer / SpO2 / MCO2)

Height: 11.4 in (28.8 cm)
Width: 9.6 in (24.4 cm)
Depth: 7.7 in (19.7 cm)
Weight: 14.4 lbs (6.5 kg)

Power Mode of Operation: Continuous

Battery Type: Sealed, gel-type lead acid **Battery Recharge Time:** 8 to 12 hours **Operating Time on Battery:** 2 hours

Display Type: Color active matrix; TFT (Thin Film Transistor) LCD Module

Resolution: 640 x 480 pixel

Active Viewing Area: 6.73 x 5.1 in. (17.09 x 12.96 cm)

Trends Parameters: NIBP, T1, T2, ΔT, HR (heart rate/pulse rate), SpO2, End-tidal CO2, Inspired

CO2, Breath Rate/Resp Rate. Assuming SpO2 and CO2 functions are present.

Duration: 5 hours for non-NIBP trends (up to 150 readings). A maximum of 128 readings

(up to 8 hours) for NIBP trends.

Printer (Optional) Operating Modes: Continuous, Snapshot, Auto Print, Auto Trend, Tabular Trend, Alarm

Print, NIBP Ticket, Apnea Ticket, OxyCRG, OxyCRG on Alarm **Auto Print Intervals:** 15 min, 30 min, 1 hour, 2 hours, 4 hours

Auto Trend Shifts: Once every 4 hours

Number of Waveforms: Up to three: ECG1, P1, P2, SpO2, CO2, RESP

Printing Speeds: 6.25, 12.5, 25.0 mm/s, simulated 6.25 mm/s for CO2 and RESP in

Snapshot mode



SOMA TECH INTL • 166 HIGHLAND PARK DRIVE • BLOOMFIELD, CT 06002 • USA PHONE: 1.800.GET.SOMA • WWW.SOMATECHNOLOGY.COM • EMAIL: SOMA@SOMATECHNOLOGY.COM