

The Philips Agilent Viridia M3 Patient Monitor is a small, lightweight contact monitor that offers flexible monitoring to suit all your monitoring needs. The Monitor can be connected to the Philips M3000A Multi-Measurement Server. The color display of the Viridia M3 has a wide viewing angle, and excellent visibility from a distance. Making it easy to recognize and see the data that is needed for decision making. For applications where multiple or larger displays are required, additional displays can be connected to the monitor through a standard VGA output. The Philips Agilent Viridia M3 patient monitor was designed for use by clinicians for adult, pediatric and neonatal patients in critical and intensive care areas, Operating Rooms and General Wards, and for transport inside and outside the hospital.

Features

- Portable
- Wireless
- Networked monitor
- EASI[™]-derived 12-lead ECG4 using a 5-electrode cable set
- Multi-lead Arrhythmia
- Up to 3 channels of ECG with basic Arrhythmia and ST Analysis capability
- FAST-SpO2 measurement, using Fourier Artifact Suppression Technology, for accurate performance even with low perfusion
- Respiration, Non-invasive and Invasive Blood Pressure, and Temperature measurements
- Mainstream or Sidestream CO2, a second Invasive Blood Pressure and Temperature measurements, and enhanced Arrhythmia capability, available optionally



SOMA TECH INTL • 166 HIGHLAND PARK DRIVE • BLOOMFIELD, CT 06002 • USA PHONE: 1.800.GET.SOMA • WWW.SOMATECHNOLOGY.COM • EMAIL: SOMA@SOMATECHNOLOGY.COM

Philips Agilent Viridia M3 Multiparameter Monitor

Specifications

Dimensions Without Handle

Width: 8.27 in (210 mm) Height: 8.27 in (210 mm) Depth: 5.31 in (135 mm)

Weight: with out battery 7.05 lbs. (3200 g)

Electrical 100 to 240VAC, 50/60Hz,

0.4 to 0.7A

Display 6.5" (diagonal) active color LCD (TFT)

Resolution: 640 × 480 pixels

VGA Interface Refresh rate: 60 Hz.

Horizontal frequency: 31.5 kHz Resolution: 640 x 480 pixels Video Signal: 0.7 Vpp @ 75 Ohm HSYNC/VSYNC signal type: TTL Connector: 15-pin D-SUB

SOMA TECH INTL • 166 HIGHLAND PARK DRIVE • BLOOMFIELD, CT 06002 • USA PHONE: 1.800.GET.SOMA • WWW.SOMATECHNOLOGY.COM • EMAIL: SOMA@SOMATECHNOLOGY.COM