

The **Philips IU22** is a full-size ultrasound that can provide imaging for; Abdominal, Gynecology, Obstetrics, Cardiac, Radiology, Pediatrics, and Musculoskeletal. The Philips IU22 is identical to the Philips IE33, the difference between them is that the IE33 system specializes in Cardio-Vascular ultrasounds imagery. The IU22 offers advanced imaging technology and can provide 2D, 3D, and 4D imaging. Along with tissue harmonic, iScan, and Contrast Specific imaging modes. The ultrasound works with a range of transducers and probes, including the PureWave Transducers. This offers a higher quality image and can be instrumental in working with difficult-to-image patients. The Philips system comes with a 21-inch LCD monitor, an 8.4-inch touch screen control panel, four transducer ports, and four USB connections. With DICOM and Ethernet connections for transferring data.

Features

- · Tissue Harmonic Imaging with Pulse Inversion technology
- Harmonic SonoCT imaging
- XRES adaptive image processing technology
- iSCAN intelligent scanning for one-button TGC, gain and compression map optimization
- iSCAN with AGC for real-time line-by-line TGC optimization
- Simultaneous 2D M-mode
- Broadband Flow imaging
- CPA
- 2D/PW Doppler
- CW/PW
- Contrast Specific Imaging (CSI)
- · Panoramic imaging with SonoCT, XRES and harmonic modes
- Freehand 3D and MPR imaging with SonoCT, XRES and harmonic modes
- Automated 3D and 4D imaging with SonoCT, XRES and harmonic modes
- Chroma imaging in 2D, 3D, 4D, MPR, Panoramic, M-mode and Doppler modes



SOMA TECH INTL • 166 HIGHLAND PARK DRIVE • BLOOMFIELD, CT 06002 • USA PHONE: 1.800.GET.SOMA • WWW.SOMATECHNOLOGY.COM • EMAIL: SOMA@SOMATECHNOLOGY.COM



Specifications

I. I	
Dimensions	Height:51 - 58 in (129.5 - 147.3 cm)
	Width:21 in (53.3 cm)
	Weight: 220 lbs
User Interface	monitor Size 20" LCD Flat panel
	Moveable Console Variable
	Adjustable monitor Variable
	Up to 500fps 2D Frame Rate (probe dependent)
	Pre-Processing
	Post-Processing
	Selectable Dynamic Range
	Adjustable Transmit Focus
	>100 multiple applications Customizable Presets
	3 Transducer Ports
Imaging Modes	2D
	M-mode
Doppler Modes	High Frame rate Color Flow
	Color Doppler Velocity
	Color Flow Mapping
	Color Doppler Energy
	Color Power Doppler
	Directional Color Power Doppler
	Directional Tissue Imaging(DTI)
	Pulse Wave (PW) YES
	Continous Wave (CW)

SOMA TECH INTL • 166 HIGHLAND PARK DRIVE • BLOOMFIELD, CT 06002 • USA PHONE: 1.800.GET.SOMA • WWW.SOMATECHNOLOGY.COM • EMAIL: SOMA@SOMATECHNOLOGY.COM

