



Tuttnauer manual autoclaves will compliment any healthcare facility and satisfy your entire sterilization needs. The bright, new, easy to use panel was designed with the operator in mind. Time tested reliability and durability are built into every Tuttnauer product.

Features

- Automatic shut off at the end of both the sterilization and dry cycles.
- A long life electro polished chamber and door.
- Double safety locking device prevents door from opening while chamber is pressurized.
- Drain valve is located on the front, allowing for quick and easy draining of water reservoir.
- Dual safety thermostat to protect against overheating.
- International certifications



Specifications

Technical Specifications

Chamber Dimensions: 10" x 19" (254 x 475 mm)
Chamber Volume: 6 gal (23 L)
Overall Dimensions LxWxH: 21.5" x 20" x 14.4" (545 x 510 x 365 mm)
Standard Cassettes Capacity: 3 full and 3 half
Tray Dimensions DxWxH: 16.3" x 6.7" x 0.8" (415 x 170 x 20 mm)
No. of Trays: 4
Standard Unwrapped Cycle Time: 30 min. cold, 14 min. hot
Voltage: 120v
Frequency: 50/60 MHz
Power: 1400W
Current: 12A
Autoclave Weight: 85 lbs (39 kg))

Speed & Volume

6 gallons
Holds 3 full and 3 half standard cassettes
Cycle time from cold start -30 minutes
Cycle time from hot start -11 minute
Adjustable to 273°F (134°C) and 30 psi

