

ICU MEDICAL LEVEL 1 H-1200



ABOUT

When lives are at stake from significant blood loss due to trauma or major surgery, the Level 1 rapid infuser fast flow fluid warmer provides a rapid flow of normothermic blood and I.V. fluids. Even a small drop in body temperature can be detrimental—delaying recovery or allowing an infection to set in. Level 1 H-1200 rapid infuser allow fast infusion of warm fluids while providing the extra level of protection of an integrated air detector/clamp. Upon detection of air in the line, the flow of blood and crystalloid is automatically stopped, allowing quick removal of air and restoration of flow without disconnecting from the patient or changing disposable administration sets. Different disposable sets are available for a variety of clinical applications.

FEATURES

- Rigid pressure chambers accommodate standard blood and crystalloid bags providing a constant 300mmHg pressure for rapid infusion.
- On/Off toggle switch used to quickly and easily pressurize chambers.
- Aluminum heat exchanger, that transfers heat 1000 times faster than plastic, and the countercurrent 42°C circulating water bath, ensure patients receive normothermic blood and I.V. fluids.
- An additional level of safety with the integrated Air Detector/Clamp that detects the presence of air in the blood and crystalloid alerts clinicians, and automatically stops the flow, and allows quick removal of air without disconnecting from the patient or changing disposables.



SPECIFICATIONS



DIMENSIONS

Height: 67 inches (1.7 m)

Width: 20 inches (51 cm)

Depth: 20 inches (51 cm)

Weight (Dry): 63 pounds (28.5 kg)

Recirculating Solution Capacity: 0.37 gallons (1.4 L)

Air Source Pressure: 300 (294 ± 6) mm/Hg

ENVIRONMENTAL

Operation Temperature: 10°C to 40°C

Transportation Temperature: -18°C to 60°C

Storage Temperature: 5°C to 40°C

Operation Humidity: 10 to 95%

Transportation Humidity: 5 to 95%

Storage Humidity: 5 to 95%

ELECTRICAL

Protection Against Electrical Shock: Class I

Equipment Type BF Equipment

Mode of Operation: Continuous

Type of Current: Alternating

Ingress Protection: Rating IPX1

MAINS Power Input (REF H-1200 115 V): 115 VAC, 60 Hz, 12 Amps

MAINS Power Input (REF H-1200 230 V): 230 VAC, 50 Hz, 6.3 Amps

Auxiliary MAINS Outlet (REF H-1200 115 V): 1.5 Amps

Auxiliary MAINS Outlet (REF H-1200 230 V): 0.75 Amps