Video Laryngoscopes

VERATHON GLIDESCOPE GO 2

ABOUT

The **Verathon GlideScope Go 2** is a portable video laryngoscope designed to provide clear airway visualization during routine and difficult intubation procedures. It features a high-resolution 3.5-inch color display, anti-glare coating and an adjustable tilt for improved viewing. Compatible with GlideScope Spectrum single-use blades, the system supports convenient setup and infection control.







FEATURES

IP67 Protection Rating: Fully submersible monitor and battery for easier cleaning.

Automatic Video Recording: Records airway procedures for review and documentation.

USB Data Transfer: Export recorded videos using a removable USB drive.

Hot-Swappable Blades: Change compatible blades without powering down the monitor.

Extended Battery Runtime: Provides at least 100 minutes of continuous use on a full charge.

Rugged Construction: Designed to withstand drops from heights of up to four feet.

Verathon GlideScope Go 2

SPECIFICATIONS

DIMENSIONS

Width: 3.86 in (98 mm)

Height: 3.39 in (86 mm)

Depth: 1.85 in (47 mm)

Weight: 0.55 lb (0.25 kg)

DISPLAY SPECIFICATIONS

Type: LCD color display

Resolution: 320 × 240 pixels

Size: 3.5 in (8.9 cm)

Frame Rate: 30 frames per second for displayed and recorded video.

BATTERY

Type: Rechargeable lithium battery

Runtime: Approximately 100 minutes under normal conditions, without recording

Charging Time: Up to 3 hours for a full charge

COMPATIBLE COMPONENTS

Single-Use Blades: GlideScope Spectrum video laryngoscopes

Reusable Component: GlideScope Video Baton 2.0 Large with GVL Stats sizes 3–4.

OPERATING CONDITIONS

Operating Temperature: 50°F to 104°F (10°C to 40°C)

Charging Temperature: 50°F to 95°F (10°C to 35°C)

Relative Humidity: 0–95%, non-condensing

ENVIRONMENTAL SPECIFICATIONS

Operating Humidity: 0–95%, non-condensing

Storage Temperature: -20°C to 40°C (-4°F to 104°F)

Storage Humidity: 10–95%, non-condensing.